


CIRCULAR SAW BLADES FOR WOOD

D mm	B mm	b mm	d mm	Z	Hook A1	NL	Freud Code	Art. No.
254	2,1	1,6	30	24	5°	-	FR24W002MC	F03FS11527
254	2,1	1,6	30	48	5°	-	FR24W003MC	F03FS11528
305	2,2	1,6	30	42	5°	-	FR29W004MC	F03FS10065
305	2,2	1,6	30	60	5°	-	FR29W005MC	F03FS10066
305	2,2	1,6	30	96	5°	-	FR29W006MC	F03FS10067



Machines:
Small table saws.

Materials:
Soft and hard solid wood, chipboard, plywood, MDF and other wood based materials.

Technical information:
ATB tooth with positive cutting angle.



For small table saws




Table saws

Corded



Softwood

Hardwood

Chipboard

Plywood

MDF

D mm	B mm	b mm	d mm	Z	Hook A1	Rip cut quality	Cross cut quality	NL	Freud Code	Art. No.
190	2,0	1,3	30	24	15°	•••	•	2/7/42	FR13W001T	F03FS09767
190	2,0	1,3	30	48	5°	•	•••	2/7/42	FR13W002T	F03FS09768
190	2,4	1,6	Star	24	15°	•••	•	-	FR13W003T	F03FS09769
190	2,4	1,6	Star	48	5°	•	•••	-	FR13W004T	F03FS09770
216	2,4	1,8	30	24	15°	•••	•	2/6/42	FR16W003T	F03FS11519
216	2,4	1,8	30	48	10°	•	•••	2/6/42	FR16W004T	F03FS11520
220	2,6	1,6	30	48	10°	••	••	2/7/42	FR17W001T	F03FS09771
225	2,6	1,6	30	32	15°	•••	•	2/7/42	FR18W001T	F03FS09772
225	2,6	1,6	30	48	10°	••	••	2/7/42	FR18W002T	F03FS09773
250	2,4	1,8	25,4	48	15	•••	•	-	FR23W005T	F03FS11641
250	2,4	1,8	25,4	60	15	••	••	-	FR23W006T	F03FS11642
250	2,4	1,8	25,4	80	15	•	•••	-	FR23W007T	F03FS11643
250	2,4	1,8	25,4	100	15	•	•••	-	FR23W008T	F03FS11644
250	2,8	1,8	30	24	20°	•••	•	2/6/42	FR23W001T	F03FS09774
250	2,8	1,8	30	40	15°	•••	•	2/6/42	FR23W002T	F03FS09775
250	2,8	1,8	30	60	10°	••	••	2/6/42	FR23W003T	F03FS09776
250	2,8	1,8	30	80	5°	•	•••	FT121	FR23W004T	F03FS09777
254	2,6	1,8	30	24	20°	•••	•	2/6/42	FR24W001T	F03FS09778
254	2,6	1,8	30	40	15°	•••	•	2/6/42	FR24W002T	F03FS09779
254	2,6	1,8	30	60	10°	••	••	FT121	FR24W003T	F03FS09780
254	2,6	1,8	30	80	5°	•	•••	FT121	FR24W004T	F03FS09781
255	2,8	1,8	25,4	40	15°	•••	•	-	FR25W002T	F03FS10134
255	2,8	1,8	25,4	60	15°	••	••	-	FR25W003T	F03FS10135
255	2,8	1,8	25,4	80	15°	•	•••	-	FR25W004T	F03FS10136
260	2,6	1,8	30	60	10°	••	••	-	FR26W001T	F03FS09782
260	2,6	1,8	30	80	5°	•	•••	FT121	FR26W002T	F03FS09783
280	2,5	1,8	30	64	10°	••	••	2/10/60	FR27W001T	F03FS11530
300	2,5	1,8	30	48	15°	•••	•	2/10/60	FR28W001T	F03FS09784
300	2,5	1,8	30	72	10°	••	••	2/10/60	FR28W002T	F03FS09785
300	2,5	1,8	30	100	5°	•	•••	FT121	FR28W003T	F03FS09786
305	2,8	1,8	25,4	96	15°	•	•••	-	FR29W002T	F03FS10138
305	2,8	1,8	30	100	5°	•	•••	2/10/60	FR29W001T	F03FS09787
355	3,0	2,2	25,4	108	15°	•	•••	-	FR33W001T	F03FS10137

FT121: 2/7/42 + 2/9/46 + 2/9,5/46,5 + 2/10/60